

TITLE OF THE INVENTION

**DOUBLE CONTROL APPARATUS CAPABLE OF SAVING POWER
AND POWER CONTROL METHOD THEREOF**

CLAIM OF PRIORITY

[0001] This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C §119 from an application entitled *Double Control Unit Capable Of Saving Power And Power Control Method Thereof* earlier filed in the Korean Industrial Property Office on 10 January 2001, and there duly assigned Serial No. 2001-1348 by that Office.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to a double control apparatus having a main control unit and an auxiliary control unit, and more particularly, to a double control apparatus capable of saving power, which can save power in a sleep mode, and a power control method performed in the double control apparatus capable saving power.

Description of the Related Art

[0003] At present in the U.S., a movement for preventing pollution by reducing energy consumption in the residential section, that is, Energy Star Residential Program, is being expanded. The goal of this program is to spread high-efficiency energy apparatuses up to 100% of households

1 by the year 2010. As a step for this program, the Environmental Protection Agency (EPA) of the
2 U.S. grants an Energy Star® label to a product complying with a predetermined standard.

3 **[0004]** Office equipment, led by computers, is the fastest growing electric load in the business
4 world. In fact, office equipment accounts for about 7 percent of all commercial sector electricity
5 usage, but much of this energy is wasted. That is because many people leave their computers,
6 printers, facsimile machines, etc., on even when they are not in use during the business day, and
7 some are even left on overnight and on weekends. The Version 2.0 of the MOU (Memorandum of
8 Understanding) Energy Star® low power guidelines for printers, facsimile machines and Printer/Fax
9 combination machines that took effect October 1, 1995 were set as shown in the following table:

10 **Table 1**

Pages per Minute (1)	Average Watts in Low Power Mode	Printer Default Time (2)	Fax Default Time
0 < ppm < 7	15W	15 minutes	5 minutes
7 < ppm < 14	30W	30 minutes	5 minutes
> 14 ppm and color high end	45W	60 minutes	15 minutes

17 (1) Based on rated print engine speed

18 (2) Default time = minimum period of time before printer or fax machine automatically enters sleep
19 mode. Printer/Fax combination products may be set at the printer default time.

20 **[0005]** Printers, for example, are typically left on 24 hours a day but are active only a small
21 percent of the time. This means that conventional printers can waste a lot of energy and money.
22 Energy Star® labeled printers automatically power down to 15 to 45 watts, depending on the number
23 of pages produced per minute. The automatic power down feature could cut a printer's electricity

1 use by over 65 percent. Accordingly, maximization of energy efficiency in electronic products under
2 development is appearing as a very critical issue.

3 **[0006]** Hereinafter, an apparatus, which has a main control unit and an auxiliary control unit, for
4 performing an intrinsic function is referred to as 'a double control apparatus'. This double control
5 apparatus has a function unit for performing the intrinsic function(s), and two control units, the main
6 control unit and the auxiliary control unit, for performing their own functions and interfacing with
7 the outside. For example, the main control unit controls the function unit for performing intrinsic
8 function(s), and the auxiliary control unit, under the main control unit's control, controls an interface
9 unit for interfacing the double control apparatus with the outside. Therefore, by virtue of the main
10 control unit and auxiliary control unit, the double control can perform its own functions, without
11 being affected by an external interrupt, that is, even when information is input by an external user.
12 For example, the double control apparatus can be a multifunctional peripheral (MFP) printer, which
13 performs printer functions together with copying, faxing, and scanning functions.

14 **[0007]** New regulations issued by the EPA, such as Energy Star® limitations, impose stricter
15 power save mode power consumption levels for printers and other image forming devices.
16 Conventional printers and other imaging forming devices will have great difficulty in meeting these
17 new limits as well as stricter limits in the future due to the above inefficiencies. Therefore, there
18 exists a need to provide devices and methodologies providing increased efficiencies.

19 **[0008]** According to the above-described Energy Star® program, the EPA now plans to enforce
20 from November 1, 2001, a standard, which requires an MFP printer to change its mode into a sleep
21 mode in which the printer consumes 15 watts or less within 30 minutes or 5 watts or less within 60
22 minutes, wherein the MFP printer is capable of printing papers between 7 sheets and 15 sheets per
23 minute.

1 **[0009]** However, the conventional MFP printer supplies power, for example, +5 volts, which is
2 provided through a switching mode power supply (SMPS), to the main control unit, auxiliary control
3 unit and function unit at the same time, and enters into the sleep mode by the main control unit.
4 Therefore, even when the holding current of a motor in the conventional MFP printer is set to 0mA
5 in a sleep mode, the conventional MFP printer needs about 2-watt power consumption of the SMPS
6 and about 7-watt power consumption of the main control unit and auxiliary control unit and
7 therefore, cannot comply with the EPA standard, which requires 5-watt or less power consumption
8 in a sleep mode.

9 SUMMARY OF THE INVENTION

10 **[0010]** To solve the above problems, it is an object of the present invention to provide a double
11 control apparatus capable of saving power in a sleep mode by an auxiliary control unit controlling
12 power used in a main control unit and a function performing unit for performing predetermined
13 functions.

14 **[0011]** It is another object to provide a power control method performed in the double control
15 apparatus capable of saving power.

16 **[0012]** To accomplish the above object of the present invention, there is provided a double control
17 apparatus, capable of saving power, having a first power supply unit for converting alternating
18 current (AC) power input from the outside into direct current (DC) power, and providing the DC
19 power as a first power; a function performing unit, which is driven in response to a second power,
20 for performing predetermined function(s); an external interface unit, which is driven in response to
21 the first power and the second power, for receiving control information from the outside and
22 outputting input state information to the outside; an auxiliary control unit, which is driven in

1 response to the first power, for receiving the control information from the external interface unit,
2 outputting the state information to the external interface unit, and in response to a sleep mode signal,
3 outputting a power control signal; a main control unit, which is driven in response to the second
4 power, for outputting the state information, which is obtained by executing a program for controlling
5 the function performing unit, to the auxiliary control unit in response to the control information input
6 from the auxiliary control unit, and generating the sleep mode signal in response to the result of
7 checking whether or not performing the predetermined function by the function performing unit is
8 completed; and a second power supply unit for outputting the first power as the second power in
9 response to the power control signal.

10 **[0013]** To accomplish another object of the present invention, there is also provided a power
11 control method performed by the double control apparatus, the method having the steps of (a)
12 generating a first power by converting an AC power into a DC power, and operating an auxiliary
13 control unit by the generated first power; (b) generating a second power and operating a function
14 performing unit and a main control unit by the generated second power; (c) continuously determining
15 whether or not a sleep mode signal is generated when a predetermined time period (default time)
16 elapses after a predetermined function is performed; (d) transmitting state information from the main
17 control unit to the auxiliary control unit if the sleep mode signal is generated; and (e) cutting off the
18 generation of the second power.

19 BRIEF DESCRIPTION OF THE DRAWINGS

20 **[0014]** A more complete appreciation of the present invention, and many of the attendant
21 advantages thereof, will become readily apparent as the same becomes better understood by
22 reference to the following detailed description when considered in conjunction with the

1 accompanying drawings in which like reference symbols indicate the same or similar components,
2 wherein:

3 **[0015]** FIG. 1 is a block diagram of a double control apparatus capable of saving power according
4 to the present invention; and

5 **[0016]** FIG. 2 is a flowchart for explaining a power control method, according to the present
6 invention, which is performed in the double control apparatus shown in FIG. 1.

7 DETAILED DESCRIPTION OF THE INVENTION

8 **[0017]** FIG. 1 is a block diagram of a double control apparatus capable of saving power according
9 to the present invention, and the double control apparatus has a first power supply unit 10, a second
10 power supply unit 18, a function performing unit 12, a main control unit 14, an auxiliary control unit
11 16, and an external interface unit 22.

12 **[0018]** A preferable embodiment of a double control apparatus capable of saving power, of the
13 present invention, shown in FIG. 1, additionally has a motor 20, and the external interface unit 22
14 has a ring detection unit 30, a key input unit 32, and a liquid crystal display (LCD) 34, which will
15 be explained later in detail.

16 **[0019]** The first power supply unit 10 converts alternating current (AC) power, which is externally
17 input through an input terminal IN1, into direct current (DC) power, and provides the converted DC
18 power, as the first power 40, to the auxiliary control unit 16, the second power supply unit 18 and
19 corresponding units 30 and 32 of the external interface unit 22. For this, the first power supply unit
20 10 can be implemented by a switching mode power supply, and converts the primary AC power into
21 DC power 40, such as +5, +12, or +30 volts.

22 **[0020]** The function performing unit 12 is driven in response to a second DC power 42 provided

1 from the second power supply unit 18, and performs predetermined functions. According to an
2 application of the present invention, the double control apparatus shown in FIG. 1 can be applied to
3 a printer. In this case, the function performing unit 12 performs a printing function as a
4 predetermined function.

5 **[0021]** According to another application of the present invention, the double control apparatus
6 shown in FIG. 1 can be applied to an ink-jet or laser MFP printer. In this case, the function
7 performing unit 12 performs additional other functions, for example, a fax function, a scanning
8 function, and/or a copying function, as well as a printing function, as predetermined functions. To
9 perform these applications, the function performing unit 12 can have a memory (not shown), a
10 modem (not shown), and an image processor (not shown).

11 **[0022]** Also, to perform a printing function, the double control apparatus capable of saving power
12 shown in FIG. 1 can additionally have a motor 20, which is driven in response to the second DC
13 power 42 provided from the second power supply unit 18, and which operates by control of the main
14 control unit 14.

15 **[0023]** Meanwhile, the main control unit 14 is driven in response to the second DC power 42
16 provided from the second power supply unit 18, and controls the function performing unit 12, the
17 motor 20 and the auxiliary control unit 16 according to a program which can be stored in a program
18 memory (not shown).

19 **[0024]** For example, the main control unit 14 outputs to the external interface unit 22 through the
20 auxiliary control unit 16, state information obtained by executing a program for controlling the
21 function performing unit 12 in response to control information input from the external interface unit
22 22 through the auxiliary control unit 16. Also, the main control unit 14 checks whether the function
23 performing unit 12 finishes performing a predetermined function or still performs the predetermined

1 function, generates a sleep mode signal in response to the result of checking, and outputs the
2 generated sleep mode signal to the auxiliary control unit 16.

3 **[0025]** For this, the main control unit 14 can internally have a counter (not shown), which counts
4 a predetermined time period when the function performing unit 12 finishes performing the
5 predetermined function, and which generates a sleep mode signal if the predetermined time period
6 is counted. For example, the predetermined time period can be 5, 15, 30 or 60 minutes. When
7 generating the sleep mode signal, the main control unit 14 outputs state information, which indicates
8 the state of the double control apparatus, to the auxiliary control unit 16.

9 **[0026]** The auxiliary control unit 16 is driven in response to the first power 40 provided from the
10 first power supply unit 10, and outputs control information input from the external interface unit 22
11 to the main control unit 14. Also, the auxiliary control unit 16 outputs a power control signal to the
12 second power supply unit 18 in response to the sleep mode signal generated by the main control unit
13 14.

14 **[0027]** When the main control unit 14 generates a sleep mode signal, the auxiliary control unit 16
15 controls the second power supply unit 18 by generating a power control signal so that the supply of
16 the second power 42 is cut off. At this time, when the sleep mode signal is received from the main
17 control unit 14, the auxiliary control unit 16 receives the state information output from the main
18 control unit 14, and outputs the received state information to the external interface unit 22.

19 **[0028]** The main control unit 14 and the auxiliary control unit 16 described above use different
20 clock signals and for this, each unit can have an oscillation circuit for generating its own clock
21 signal.

22 **[0029]** Meanwhile, in response to the power control signal output from the auxiliary control unit
23 16, the second power supply unit 18 outputs the first DC power 40 provided from the first power

1 supply unit 10 to the function performing unit 12, the main control unit 14, and the LCD 34, as the
2 second DC power 42. For this, the second power supply unit 18 can be implemented by a power
3 transistor (not shown). In this case, in response to a power control signal generated by the auxiliary
4 control unit 16 when a sleep mode signal is generated, the power transistor (not shown) of the second
5 power supply unit 18 turns off so as not to generate the second DC power 42, and in response to a
6 power control signal generated by the auxiliary control unit 16 when a sleep mode signal is not
7 generated the power transistor (not shown) turns on so as to generate the second DC power 42.

8 **[0030]** Meanwhile, the external interface unit 22 is driven in response to the first DC power 40
9 provided from the first power supply unit 10 and the second DC power 42 provided from the second
10 power supply unit 18. First, the external interface unit 22 has an LCD 34 which is driven in response
11 to the second DC power 42 so that state information input from the main control unit 14 through the
12 auxiliary control unit 16 can be displayed to an external user. Also, the external interface unit 22
13 has a key input unit 32 for receiving externally input control information and for outputting control
14 information to the main control unit 14 through the auxiliary control unit 16. The key input unit 32
15 is driven in response to the first DC power 40, has a plurality of keys, and outputs, as a result of the
16 user's manipulation of the keys, control information to the main control unit 14 through the auxiliary
17 control unit 16.

18 **[0031]** Meanwhile, according to a preferable embodiment of the present invention, the auxiliary
19 control unit 16 can generate the power control signal for turning on the second power supply unit
20 18 to generate the second DC power 42 in response to the control information input through the
21 external interface unit 22, as described above, after the supply of the second DC power 42 from the
22 second power supply unit 18 is cut off.

23 **[0032]** Additionally, the external interface unit 22 has a ring detection unit 30, which is driven in

1 response to the first DC power 40, detects a ring signal received through the input terminal IN2 from.
2 for example, a public switched telephone network (PSTN: not shown), and outputs the detected ring
3 signal to the auxiliary control unit 16 as the control information. Therefore, during the sleep mode
4 in which the supply of the second DC power 42 is cut off in response to the power control signal
5 generated in response to the sleep mode signal, if control information from the ring detection unit
6 30 is input to the auxiliary control unit 16, the auxiliary control unit 16 controls the second power
7 supply unit 18 by generating a power control signal so that the second power supply unit 18 is
8 turned on and the second DC power 42 is regenerated.

9 **[0033]** A power control method performed in the double control apparatus capable of saving
10 power according to the present invention, shown in FIG. 1, will now be further explained. At this
11 time, a state in which the second DC power 42 is not generated in response to the generated sleep
12 mode signal is defined as 'a sleep mode'. Also, a state in which the function performing unit 12
13 continues to perform the predetermined function, the predetermined period does not elapse yet
14 though performing the predetermined function is completed, or the second DC power 42 is
15 regenerated by new control information input from the external interface unit 22 after the second
16 power 42 is cut off, is defined as 'an idle mode'.

17 **[0034]** FIG. 2 is a flowchart for explaining a power control method, according to the present
18 invention, which is performed in the apparatus shown in FIG. 1, and the power control method
19 includes steps 50 and 52 for generating the first power 40 and the second power 42, and the steps
20 54 through 58 for cutting off the generation of the second power 42 according to whether the sleep
21 mode signal is generated or not.

22 **[0035]** A preferable embodiment according to the present invention of the power control method
23 shown in FIG. 2 additionally includes steps 60 and 62 for regenerating the second power 42

1 according to the control information input from the outside during a sleep mode when the first power
2 40 is continuously generated. This will be explained later.

3 **[0036]** In the power control method, according to the present invention, performed in the double
4 control apparatus shown in FIG. 1, first, the auxiliary control unit 16, the ring detection unit 30, and
5 the key input unit 32 are driven by the first power 40 obtained by converting AC power input through
6 the input terminal IN1 in the first power supply unit 10 into DC power in step 50.

7 **[0037]** After the step 50, the second power 42 is generated, in step 52, in an idle mode in response
8 to the power control signal generated by the auxiliary control unit 16, thus the second power supply
9 unit 18 drives the function performing unit 12, the main control unit 14, the motor 20, and the LCD
10 34.

11 **[0038]** Following step 52, the main control unit 14 continuously determines, in step 54, whether
12 or not a predetermined time period elapses after performing a predetermined function is completed
13 by function performing unit 12. For this, the main control unit 14 counts the predetermined time
14 period using the embedded counter (not shown) after the function performing unit 12 performs the
15 predetermined function and generates the sleep mode signal when the predetermined time period
16 elapses.

17 **[0039]** When the predetermined time period elapses after performing the predetermined function
18 is completed and the sleep mode signal is generated, the main control unit 14 transmits, in step 56,
19 , the generated sleep mode signal to the auxiliary control unit 16 as state information indicating that
20 the generation of the sleep mode signal has occurred.

21 **[0040]** In response to the state information indicating that the generation of the sleep mode signal
22 has occurred, the auxiliary control unit 16 outputs, in step 58, a power control signal for cutting off
23 second power supply unit 18 to stop the generation of the second power 42. Accordingly, the double

1 control apparatus shown in FIG. 1 enters into the sleep mode.

2 [0041] According to a preferable embodiment of the present invention, after the step 58, the
3 auxiliary control unit 16 determines whether or not the first power 40 is continuously generated from
4 the first power supply unit 10, in step 60. If the first power 40 is not continuously generated, the
5 auxiliary control unit stops its operation, and all operations of the double control apparatus shown
6 in FIG. 1 stop.

7 [0042] When it is determined in step 60 that the first power 40 is continuously generated, the
8 auxiliary control unit 16 continuously determines, in step 62, whether or not control information is
9 externally input via the external interface unit 22 until the externally input control information is
10 detected. That is, if control information is input from external interface unit 22 during the sleep
11 mode, the auxiliary control unit 16 outputs a control power signal to turn on the second power
12 control unit 18 so that the second power supply unit 18 outputs the second power 42.

13 [0043] According to the above description, when in the sleep mode, power consumption of first
14 power supply unit 10 is 2 Watts or less , of auxiliary control unit 16 is 0.5 Watts or less, of ring
15 detection unit 30 is 0.1 Watts or less and of key input unit 32 is 0.5 Watts or less.

16 [0044] As described above, the double control apparatus capable of saving power and the power
17 control method according to the present invention can meet the stricter Energy Star® requirement
18 of the 5-watt or less power consumption in the sleep mode, when applied to an SMPS-type ink-jet
19 printer or laser MFP printer, and can reduce costs because the apparatus uses the auxiliary control
20 unit in the double control unit to control power so that separate devices for power control according
21 to the present invention be not needed.